

AK Glass

Product Code: 430-SR

Product Series: Coated Glass Fabric



Technical Data Sheet

PRODUCT APPLICATION

Silicone Coating Glass Fabric applications are excellent for use as thermal barriers, removeable insulation pads and covers, welding curtains, blankets and pads and heat shields.

PRODUCT CHARACTERISTICS

- High temperature resistant
- Abrasion resistant
- Flexible for use in pad fabrication
- Durable for use in severe environments

PHYSICAL PROPERTIES

Coating Agent	Silicone Rubber
Weight	540 g/m ²
Weave Style	Satin
Thickness	0.43 mm
Working Temperature	< 260 ° C
Color	Grey

DIMENSION

Roll Width	1550 mm
Roll Length	50 m

Safety

Obtain, read, and understand the Material Safety Data Sheet (SDS) before use of AK Glass and AK Carbon Products
FOR FURTHER INFORMATION, PLEASE CONTACT US



IA KANGNAM COMPANY LIMITED

/1 Moo 6, Tambol Thakam, Amphur Bangpakong,

Chachoengsao, 24130 Thailand

Phone: (+66) 38 573 635

Fax: (+66) 38 573 636, (+66) 38 573 734

This information and data contained herein is offered solely as a guide in the selection of a reinforcement material. The information contained in this publication is based on actual laboratory data and field test experience. We believe this information to be reliable, but do not guarantee its applicability to the user's process. The user agrees to be responsible for thoroughly testing any application to determine its suitability before committing to production. The values listed for weight, thickness, and breaking strength are greige values, unless otherwise noted. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose.