

# AK Glass

Product Code: RB16

Product Series: Glassfiber Tape



## Technical Data Sheet

### PHYSICAL PROPERTIES

Type of Glass			C - Glass
Weave Style	Plain		
	<u>SI</u>	<u>US</u>	<u>Testing Standard</u>
Thickness	1.6 mm		ASTM D1777
Moisture Content	≤ 0.5%		ASTM D4963
Breaking Strength	≥ 300 N/20mm		ASTM D5035
Temperature Resistance	≤ 500 ° C		

### DIMENSION

Roll Width		1, 2 in	ASTM D3774
Roll Length	30 m		ASTM D3773

### Safety

Obtain, read, and understand the Material Safety Data Sheet (SDS) before use of AK Glass and AK Carbon Products

*FOR FURTHER INFORMATION, PLEASE CONTACT US*



#### ASIA KANGNAM COMPANY LIMITED

69/1 Moo 6, Tambol Thakam, Amphur Bangpakong, Chachoengsao, 24130 Thailand

Phone: (+66) 38 573 635

Fax: (+66) 38 573 636, (+66) 38 573 734

This information and data contained herein is offered solely as a guide in the selection of a reinforcement material. The information contained in this publication is based on actual laboratory data and field test experience. We believe this information to be reliable, but do not guarantee its applicability to the user's process. The user agrees to be responsible for thoroughly testing any application to determine its suitability before committing to production. The values listed for weight, thickness, and breaking strength are greige values, unless otherwise noted. Because of numerous factors affecting results, we make no warranty of any kind, express or implied, including those of merchantability and fitness for a particular purpose.